



SAFE-WAY

GARAGE DOORS

Make a Statement

Choice Series

30, 31, 32 & 33 Residential

300, 301, 302, 303, 310, 311, 312 & 313 Commercial



Model 31
Detail

* Photos shown with painted doors.



Versatility at a Great Value

Safe-Way's flush wood doors offer an economical choice for beauty and versatility. These quality overhead doors have the look and feel of smooth or richly textured wood all offering strength and durability. Available for residential or commercial applications, our flush wood models beautify your home or business with style and dependable performance.

Make a Statement.



Product Features & Description Chart


Model #	Description	Thickness	R-Value	Max Width	Max Height
30	Smooth finish	1-1/4"	6.0	18'	8'
31	Ruf-Sawn inside and out	1-1/4"	6.0	18'	8'
32	Luaun finish inside and out	1-1/2"	6.0	18'	8'
33	Smooth inside Ruf-sawn out	1-1/4"	6.0	18'	8'
310	Smooth finish	1-1/4"	6.0	18'2"	12'
311	Ruf-Sawn inside and out	1-1/4"	6.0	18'2"	12'
312	Luaun finish inside and out	1-1/2"	6.0	18'2"	12'
313	Smooth inside Ruf-sawn out	1-1/4"	6.0	18'2"	12'
300	Smooth finish	1-3/4"	8.5	16'2"	16'
301	Ruf-Sawn inside and out	1-3/4"	8.5	16'2"	16'
302	Luaun finish inside and out	2"	8.5	16'2"	16'
303	Smooth inside Ruf-sawn out	1-3/4"	8.5	16'2"	16'

* Consult factory on sizes beyond those listed above.


Product Features & Specifications

- Expanded polystyrene insulating core is pressure bonded between two skins with waterproof adhesive to a solid wood frame.
- Models 30, 300 and 310 have a smooth finish. Models 31, 301, and 311 have a "Ruf-Sawn" look that simulates a wood grain texture. Models 32, 302 and 312 have a luaun wood finish inside and out. Models 33, 303 and 313 have a "Ruf-Sawn" look with a smooth inside.
- Hardware is manufactured out of hot dipped galvanized steel. Hinges are 14 gauge and rollers are nylon. 300 series doors have 10 ball steel rollers.
- Track is available in 2" or 3". Vertical Lift, High Lift, Follow The Roof Slope, and Low Headroom options are available depending on the model. Consult your dealer for details.
- Doors are balanced by a torsion spring counterbalance system constructed of oil tempered torsion springs. High cycle spring options of 50,000 or 100,000 are available.
- A keyed lockbar locking system is available.

Product Finishes



Smooth



Ruf-Sawn



Luaun

Construction

- Top Rail
- Polystyrene Core
- Hardboard Panels
- Bottom Rail
- Actual Thickness Varies (See Above Chart for Model Specific Thickness)



Distributed by:



As Safe-Way Door constantly strives to improve our product, all specifications listed in this informative brochure are subject to change without notice or obligation. Printed color may vary from actual color, please check with your local dealer for color swatches.
2010 E-20-140



SAFE-WAY
GARAGE DOORS

Make a Statement

3814 East U.S. 30 • Warsaw, IN 46580
574-267-4861 • Fax: 574-267-2871
safe-waydoor.com